Issue Date: July 24, 2023

Material Safety Data Sheet

NFPA HMIS



Health Hazard	0
Fire Hazard	1
Reactivity	0

Issuing Date July 24, 2023 Revision Date - Revision Number 0

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name TRIAX POWERFLUID 450 Power Steering Fluid

Product / Fluid Code F343, F004, F043

Recommended Use POWER STEERING SYSTEMS AND VEHICLE HYDRUALICS

Manufactured by: TRIAX LUBRICANTS LLC

753 PORT AMERICA, SUITE 207, GRAPEVINE, TX 76051

Phone: 214-897-6533

Emergency Telephone Number CHEMTREC

1 (800) 424-9300

International: +011(703) 527-3887

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance Clear light yellow Physical liquid Odor Petroleum odor

liquid State

Classification of the substance or mixture according to CLP criteria

Classification (REGULATION (EC) No 1272/2008):

Based on available data this substance / mixture does not meet the CLP classification criteria.

Label elements

Labelling (REGULATION (EC) No 1272/2008) **Hazard pictograms:** No Hazard Symbol required

Signal word: No signal word

Hazard statements:

PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP criteria.

HEALTH HAZARDS: Not classified as a health hazard under CLP criteria.

ENVIRONMENTAL HAZARDS: Not classified as environmental hazard according to CLP criteria.

Potential Health Effects

Principal Routes of Exposure Eye contact, Skin contact, Inhalation, Ingestion

Acute Toxicity

Eyes Eye contact may result in slight irritation and redness.

Skin Substance minimally irritating upon direct contact.

Inhalation Low hazard at standard temperatures and pressures. Inhalation of oil mist or

fumes can cause irritation of the nose, throat and upper respiratory tract

Issue Date: July 24, 2023

Ingestion Do not ingest. Ingestion may cause gastrointestinal irritation, nausea, vomiting

and diarrhea.

Other On rare occasions, prolonged and repeated exposure to oil mist poses a risk of

pulmonary disease such as chronic lung inflammation. This condition is usually

asymptomatic as a result of repeated small aspirations.

Chronic Effects Prolonged exposure may cause chronic effects.

Aggravated Medical Conditions Personnel with pre-existing skin disorders should avoid contact with this

product.

Environmental Hazard See Section 12 for additional Ecological Information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula Mixture

Chemical Name	CAS-No	Weight %
Lubricant Base Oil (Petroleum) Highly	Mixture*	60-80%
refined mineral oils (C15-C50) Gr III		

This product does not contain known hazardous materials at the \geq 1% level or known carcinogens at the \geq 0.1% level as defined by 29 CFR 1910.1200.

**The exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Eye Contact Flush with large amounts of water for 15 minutes. Get medical attention if eye irritation

develops or persists. If material is hot, treat for thermal burns and take victim to the hospital

immediately.

Skin Contact Wash off immediately with soap and plenty of water for at least 15 minutes while removing

all contaminated clothing and shoes. Get medical attention immediately if skin discoloration

occurs.

Inhalation This material is not expected to present an inhalation exposure at ambient conditions.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Get

immediate medical attention or advice.

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties NOT FLAMMABLE

Flash Point >400 °F

Suitable Extinguishing Media Water fog, Foam, CO₂, dry chemical

Unsuitable Extinguishing Media Not Available

X POWERFLUID 450 SYNTHETIC Issue Date: July 24, 2023

Hazardous Combustion Products Not Available

Explosion Data

Sensitivity to Mechanical Impact Not sensitive.
Sensitivity to Static Discharge Not sensitive.

Protective Equipment and Precautions for

Firefighters

Wear positive pressure self-contained breathing apparatus (SCBA). Use water to cool containers exposed to flames. Structural firefighters' protective clothing will only provide limited protection. Mist or sprays may be flammable below the product normal

flash point.

NFPA Health 0 Flammability 1 Stability 0 Physical and Chemical

Hazard Hazards

6. ACCIDENTAL RELEASE MEASURES

Personal PrecautionsUse personal protective equipment. Avoid contact with skin, eyes, and clothing.

Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces

to become very slippery.

Methods for Containment Dike far ahead of liquid spill for later disposal.

Methods for Cleaning Up Pick up free liquid for recycle and/or disposal. Residual liquid and/or solid can be

absorbed on inert material.

Evacuation Procedures

Large Spill

Fire

Consider initial downwind evacuate for at least 300 meters (1000 feet).

If tank, rail car or tank car is involved in a fire, isolate for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions.

Reporting Requirements Spills that enter a water body must be reported immediately to the USEPA's

National Response Center at (800)424-8802. Check with your local and state

regulators regarding their reporting requirements.

7. HANDLING AND STORAGE

Handling Do not pressure, cut, weld, braze, solder, drill, grind, or expose such containers to heat,

flame, sparks, static electricity, or other sources of ignition; they may explode. See NFPA 30

and OSHA 1910.106 - flammable and combustible liquids.

Storage Store away from heat, sparks, open flame, or strong oxidizing agents in closed and properly

labeled containers. Empty containers retain product residue (liquid, and/or vapor) and can

be dangerous

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Highly Refined Petroleum	5 mg/m3 8 hour(s). Form:	5 mg/m3 8 hour(s). Form:	2,500 mg/m3
Oils Mixture	Mist	Mist	-
Detergent/Inhibitor System		5 mg/m3 8 hour(s). Form:	
Mixture		Mist	



Engineering Measures

TRIAX POWERFLUID 450 SYNTHETIC Issue Date: July 24, 2023

Additional area ventilation or local exhaust may be required to maintain air

concentrations below recommended limits.

Personal Protective Equipment

Eye/Face Protection Safety glasses or face shield where splashing is possible. Full face-shield to

be worn during emergencies.

Skin and Body As needed to prevent repeated skin contact. Solvent resistant gloves should

Protection be used if needed.

Respiratory Protection Not normally needed. During emergencies wear respirator.

Remove and wash contaminated clothing before re-use. Wash hands before **Hygiene Measures**

breaks and immediately after handling the product.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear light yellow liquid Odor Mild Petroleum Oder

Physical State Liquid pН

>400 °F Flash Point >315°C /600°F Autoignition

Temperature

Freezing Point <-25°C / < -0.4°F **Boiling Point/Range** No data

Explosion Limits N/A Flammability Limits in N/A

Air

0.86 - 0.88Solubility **Specific Gravity** Negligible **Evaporation Rate Vapor Pressure** N/A < 0.01

Vapor Density Not Determined Density N/A

10. STABILITY AND REACTIVITY

Stability STABLE under recommended storage conditions and room temperature.

Incompatible Products Open Flame and strong oxidizing agents.

Conditions to Avoid Heat, flames, and sparks.

Hazardous Decomposition

Products

Combustion products may include smoke, fumes, oxides of phosphorus, boron, sulfur, nitrogen, carbon dioxide, carbon monoxide, and other low

molecular weight hydrocarbons.

Hazardous Polymerization None under normal processing.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information Test on similar materials show a low order of acute oral and dermal toxicity.

Acute Oral

Skin Effects

Effects

Test on similar materials indicates low order of acute toxicity.

Acute Inhalation

Effects

Low acute toxicity expected on inhalation.

Practically non-toxic if absorbed. Other similar highly refined products have not

shown skin tumors in mouse skin painting studies.

Minimal irritation on contact. Eye irritation slightly or practically non-irritating base on **Eye Irritation**

similar products.

Component Information

Chemical Name LD50 Oral LD50 Dermal LC50 Inhalation

TRIAX POWERFLUID 450 SYNTHETIC MSDS NO 434440018/2

Issue Date: July 24, 2023

Highly Refined Petroleum	Not Available	Not Available	Not Available
Oils Base Oils Mixture			

Chronic Toxicity

Chronic Toxicity Prolonged exposure may cause chronic effects. On rare occasions, prolonged and

repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. This condition is usually asymptomatic as a result of repeated small

aspirations.

Carcinogenicity Not considered a potential carcinogen base on IP346 DMSO of less than 3.0 wt%

Target Organ Effects Respiratory system, Eyes, Skin,

Genotoxicity This product is considered non-mutagenic and has negative potential for tumor

development based on from Modified Ames Assay, with Mutagenic Index of less than

1.0.

12. ECOLOGICAL INFORMATION

Ecotoxicity If applied to leaves, this product may kill grasses and small plants by interfering with

transpiration and respiration. This product is not toxic to fish but may coat gill structures resulting in suffocation if spilled in shallow, running water. Product may be moderately toxic to amphibians by preventing dermal respiration. This product may cause gastrointestinal distress to birds and mammals through ingestion during

pelage grooming.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Microtox	Daphnia Magna (Water Flea)
Highly Refined Petroleum Oils	Not Available	Not Available	Not Available	Not Available
Mixture				

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method Dispose of in accordance with local regulations. Keep this product out of sewers

and waterways.

Contaminated Packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	DSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
X	Χ	X	Χ	Χ	X	Χ	Χ

U.S. Federal Regulations

SARA 313

TRIAX POWERFLUID 450 SYNTHETIC MSDS NO 434440018/2

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Issue Date: July 24, 2023

SARA 311/312 Hazard Categories

Acute Health Hazard No
Chronic Health Hazard No
Fire Hazard No
Sudden Release of Pressure No
Hazard

Reactive Hazard No

Clean Water Act

If spilled into navigable waters it is reportable to National Response Center, 800-424-8802. Reportable Quantity = Oil Sheen present on navigable water surface. (40 CFR 116; 401.15)

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

Florida

No listed ingredients are present

Massachusetts RTK

No listed ingredients are present

Minnesota RTK

No listed ingredients are present

New Jersey RTK

Lists petroleum oil, but this product does not contain hazardous ingredients.

Pennsylvania RTK

Lists petroleum oil, but this product does not contain hazardous ingredients greater than 3%.

Illinois DOL TSL

No listed ingredients are present

International Regulations

Mexico – Grade No information available.

Canada Not listed on the Canadian Controlled Product Ingredient Disclosure and is compliant

with Controlled Products Regulation

CONEG Metals Since cadmium, chromium, lead and mercury are not detectable and it does not exceed

100ppm total in this product, it is compliant with CONEG Metals regulation.

EEC (Europe) This product is not known to be a dangerous good internationally.

R-Phrases R45: May Cause Cancer

S-Phrases S53: Avoid exposure - obtain special instructions before use.

S45: In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

Hazard Label None Danger Symbol None

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

Issue Date: July 24, 2023

Prepared By Andrew Swanson Issuing Date July 24, 2023

Revision Date - New

Disclaimer

The information provided on this MSDS is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End MSDS